



HF4 Hydro Pet

With All Floor Nozzle

PRODUCT INFO:

- HF4 Hydro Pet All Floor
- HF410YP3 011
- 39401051
- EAN 8059019096414

WEIGHT AND DIMENSIONS:

- NET WEIGHT [KG]: 2,63
- PACKED WEIGHT [KG]: 7,06
- PRODUCT DIMENSIONS (WxDxH) [mm]: 258*220*1110
- PACK DIMENSIONS (WxDxH) [mm]: 711*323*142

COLOR SCHEME:

- Urban Black
- Petrol Blue

ACCESSORIES:

- Crevice tool
- 2in1 dusting brush
- Dust Bin cleaning tool
- Wall mount and 2 screws
- Motorised Pet tool
- Detergent
- Extra set of mops

3-year warranty

Subject to registration within 30 days from purchase on go.he.services/3yrs-we. Terms and conditions apply.

NEW HOOVER CORDLESS STICK HF4 HYDRO PET ALL FLOOR

360° MANEUVERABILITY EVEN FOR THE TIGHTEST⁴ SPACES



UP TO 150 AW¹ (Turbo mode)



UP TO 60 MIN RUNTIME²



HYDRO NOZZLE



MAIN FEATURES

- **Brushless motor: 240W** to generate up to 150AW¹ in Turbo mode
- Runtime² Standard Mode: up to 30 min
- Runtime² Turbo Mode: up to 15 min
- **NEW ECO Mode** Runtime: up to 60 min (handheld configuration, ECO mode)
- **25.2V/ 2500mAh** Lithium-Ion Battery pack supplied for 63Wh consumption
- **Up to 1.200 POWERTIME (Airwatts x Runtime):** up to **42 AirWatt** Suction Power X **30 minutes** or more Runtime³
- Separation System: Throw off with removable pre-motor and exhaust filter
- 360° Maneuverability to reach the tightest spaces⁴
- Bin Capacity: **0.7L**
- **NEW 3 modes for every need:** Turbo, Standard, Eco
- **NEW Intuitive UI** showing battery status, alerts and power mode + recognition of Hydro nozzle
- Removable and washable filters
- Removable battery pack, easy to charge everywhere
- Charging time: 3.5 hours

ALL FLOOR NOZZLE

- Main motorized nozzle with frontal LED lights ideal for All Floors
- Brushbar status indicator
- **ANTI-TWIST™** to prevent hair wrapping around the brushbar
- Convenient nozzle window release and access of the brushbar from the top

HYDRO NOZZLE

- **2 rotating mops and 1 vibrating triangular mop for advanced edge washing**
- 3 adjustable water levels and UV-C light feature

¹AW measured according to IEC62885-4:2020 at tube end; based on internal tests.

²Run time measured with main motorized nozzle.

³Suction power AW measured according to IEC62885-4:2020 at tube end; runtime measured with nozzle attached according to IEC62885-4:2020 on carpet and hard floor; based on internal tests with default operating modes allowing for c. 20 minutes or more runtime.

⁴Using either the main nozzle or the accessories.