HF2 Home with

Hard Floor Nozzle

PRODUCT INFO:

- HF2 Home Hard Floor
- HF201H 011
- 39401038
- EAN 8059019084176

WEIGHT AND DIMENSIONS:

- NET WEIGHT [KG]: 2,07
- PACKED WEIGHT [KG]: 3,50
- PRODUCT DIMENSIONS (WxDxH) [mm]: 259*204*1103
- PACK DIMENSIONS
 (WxDxH) [mm]: 547*276*156

COLOR SCHEME:

- Urban Black
- Midnight Magenta

ACCESSORIES:

- Crevice tool
- Wall mount with cable winder and 2 screws



Subject to registration within 30 days from purchase on go, he services/3yrs-we. Terms and conditions apply

NEW HOOVER CORDLESS STICK HF2 with ULTRA COMPACT X3™

ULTRALIGHT CLEANING WITH SURPRISING PERFORMANCE





MAIN FEATURES

- Brushless motor: 165W to generate up to 25AW¹ (standard mode)
- Runtime² Standard Mode: up to 20 min
- Runtime² Turbo Mode: up to 10 min
- **NEW ECO** Mode Runtime: up to 40 min (in Handheld configuration using the crevice tool)
- 14.4V/ 2500mAh Lithium-Ion Battey pack supplied for 36Wh consumption
- Up to **500 LAW**³ (Lasting AirWatt)
- Capable of picking up 99% of dust on hard floors⁴
- **ULTRA COMPACT X3™** compacting the dust to extend suction power and maximize bin capacity
- ULTRALIGHT: less than 1.3 kg in Handheld
- · Separation System: Single Cyclone
- Bin Capacity: 0.33L tripled to 1L⁵ thanks to ULTRA COMPACT X3[™]
- Intuitive UI showing battery status, alerts and power mode
- Turbo/ECO Button
- Integrated soft crevice in the Handheld
- · Removable and washable EPA filter
- · Removable battery pack, easy to charge everywhere
- Charging time: 3.5 4 hours
- hOn app for extra contents

HARD FLOOR NOZZLE

- Main motorized nozzle with frontal LED lights ideal for Hard Floors
- Brushbar status indicator (through flashing frontal LED lights)
- ANTI-TWIST™ to prevent hair wrapping around the brushbar
- · Convenient nozzle window release and access of the brushbar from the side

¹AW measured according to IEC62885-4:2020 at tube end, with powered nozzle; based on internal tests.

²Run time measured with main motorized nozzle.

³Up to 25 AirWatt Power X 20 minutes or more Runtime. Suction power AW measured according to IEC62885-4:2020 at tube end, with powered nozzle; runtime measured with nozzle attached according to IEC62885-4:2020; based on internal tests.

⁴On flat hard floors. Tested internally according to IEC 62885-2 Clause 5.3 in turbo mode

⁵Gross volume, Equivalent net volume 0.75L