60cm Series 9 Integrated Triple Zone Refrigerator

Series 9 | Integrated

Panel Ready | Right Hinge



Pair with the Integrated Triple Zone Freezer for the ultimate kitchen solution – this model features three independent food zones taking cooling flexibility to a new level.

- Three independent food zones, each with adjustable temperature to store different foods
- Panel ready, flush fit design with 4mm gaps and custom height installation
- Convenient access to fresh, chilled water with internal water dispenser

Easy-to-use touch-control panel and Wi-Fi capability

DIMENSIONS

Height 1870 mm
Width 592 mm
Depth 576 mm

FEATURES & BENEFITS

Three Levels Of Freshness

When it comes to optimal food preservation, one temperature does not fit all. Three independent food zones give you full control over the way you care for food. The Fridge zone has adjustable temperature from 1 to 6°C, while the bottom two compartments can be converted into a Fridge (1 to 6°C), Pantry (11 to 13°C) or Chill zone (-1.5 to 0°C), to best suit different types of food. Adjust temperature for everyday convenience, or to provide additional chilling capacity for special occasions.

Perfect Fit

These models fit flush, with only 4mm gaps around them and no visible hinges or grilles. Our Integrated models can be seamlessly hidden behind your cabinetry, or you can purchase our stainless steel door panel.

Mix & Match

These modular refrigerators and freezers can be mixed and matched, with different sizes and finishes. Installed side by side or individually throughout the kitchen, you can create a cooling solution to suit your lifestyle. Customise with your own kitchen cabinetry and handles, or purchase our stainless steel door panel and handle options.

Slimline Water Dispenser

The slimline water dispenser is located inside this Integrated model, leaving an uninterrupted exterior that blends in seamlessly with surrounding cabinetry. The flush fit design maximises internal storage space, with a temperature-controlled flow and an angled water delivery to reduce drips and spills.

Clever Energy

ActiveSmart™ Foodcare learns how you live. It is technology that understands how you use your refrigerator and adjusts temperature, airflow and humidity inside to help keep food fresher for longer.

Simple Installation

Our Integrated products are easy to install, whether you are renovating your kitchen or designing a new one. Adjustable front and rear feet allow for uneven floors alongside adjustable door panels that can be customised to match your kitchen. These models are designed to easily slide into place as separate units – a perfect fit for European design kitchens.

Ease Of Use

Using the intuitive touch-sensitive control panel, you can easily adjust the temperature to suit. Beautiful to use, the refrigerator door is family safe with a soft-close mechanism.

SPECIFICATIONS

Accessories (included)

Hinge change (from right hinge to left hinge)

Accessories (sold separately)

Door panel set stainless steel

Right & Left hinge RD6019

Handle kit Classic	AHCLRDSF
Handle kit Contemporary round, aluminium	AHSRDSF AHD5RDSF
Handle kit Contemporary square fine, aluminium	
Handle kit Contemporary square fine, black	AHD5RDSFB
Handle kit Professional round flush	AHP3RDSF
Joiner kit	AJRS19LR
Toe kick stainless steel 1200mm	AKRS12010
Toe kick stainless steel 1800mm	AKRS18010
Toe kick stainless steel 600mm	AKRS06010
Water filter replacement	847200 - FWC3
Capacity	
Total gross capacity	330 L
Volume	306 L
Volume refrigerator	306 L
Consumption	
Energy rating	С
Energy usage	114kWh/year
Features	
Adjustable door shelves	4
Adjustable glass cantilevered shelves	•
Covered door shelves	1
Door alarm	•

Internal water dispenser

LED bin lighting

LED ceiling lighting

LED side lighting	•
SmartTouch control panel	•
Stackable bottle holders	2
Water tank capacity	1 L

Installation Dimensions

Minimum inside width of cabinetry frame	600 mm
Minimum internal depth of cabinetry	600 mm
Minimum internal height of cabinetry	1880 mm

Performance

$ActiveSmart^{\scriptscriptstyleTM}$ Foodcare	•
Adaptive defrost	•
Frost free	•
Humidity control system	•
Humidity controlled crisper bins	4
Inverter controlled compressor	•
Sabbath mode	•
Triple evaporator	•
Variable food modes	Pantry; Fridge; Chill
Variable temperature zones	3

Power requirements

Amperage	10 A
Supply frequency	50 Hz
Supply voltage	230 V

Product dimensions

Depth	576 mm
Height	1870 mm
Width	592 mm

Warranty

Parts and labour	2 years
Sealed system parts only	5 years

SKU	26217

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

 □ 2D-DWG Integrated Refrigeration - K08 Hinge

 □ 2D-DWG Refrigerator

 □ 2D-DWG Refrigerator with Custom Panel

 □ 2D-DXF Integrated Refrigeration - K08 Hinge

2D-DXF Integrated Reinigeration

2D-DXF Refrigerator

2D-DXF Refrigerator with Custom Panel

2D-DXF Integrated Refrigeration - Panel Preparation

↓ Archicad 23 Refrigerator

Declaration of Conformity Refrigeration with WiFi Capability

↓ Declaration of Conformity

QUICK REFERENCE GUIDE > RS6019S3RH1 Date: 30.10.2024 > 3

- ↓ Energy Label
- ↓ Installationsvejledning DA
- ↓ Installationsanleitung DEU
- Installatiehandleiding DUT
- ↓ Guía de instalación ES
- J. Asennusopas FIN
- ↓ Guide d'installation FR
- ↓ Guida d'installazione ITA
- ↓ Installasjonsveiledning NOR
- ↓ Planning Guide Integrated Refrigeration
- J. Product Information Sheet
- ↓ Revit 18 Refrigerator
- Rhino 5 Refrigerator
- Rhino 5 Refrigerator with Custom Panel
- Rhino 5 Refrigerator Door with Classic Round Handle
- Rhino 5 Refrigerator Door with Contemporary Round Handle
- Rhino 5 Refrigerator Door with Professional Round Flush
- ↓ Rhino 5 Refrigerator Door with Square Fine Black Handle
- ↓ Rhino 5 Refrigerator Door with Square Fine Handle
- ↓ Sketchup 8 Refrigerator
- Sketchup 8 Refrigerator with Custom Panel
- Sketchup 8 Refrigerator Door with Classic Round Handle
- Sketchup 8 Refrigerator Door with Contemporary Round
- Sketchup 8 Refrigerator Door with Square Fine Black Handle
- ↓ Sketchup 8 Refrigerator Door with Square Fine Handle
- ↓ Brugervejledning DA
- J. Benutzerhandbuch DEU

- User Guide Integrated Refrigerator & Freezer
- User Guide Integrated Refrigerator Freezer EN
- Guía del usuario ES
- Käyttöopas FIN
- ↓ Guide d'utilisation FR
- ↓ MMMMMHEB
- Guida dell'utente ITA
- Brukerhåndbok NOR
- ↓ Användarmanual SWE

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



A PEACE OF MIND SALE 24 Hours 7 Days a Week Customer Support

T 08000886605 Wwww.fisherpaykel.com