QUICK REFERENCE GUIDE > WB60SDEB2

Warming Drawer, 60cm

Series 9 | Minimal

Black



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Minimal design.

- A companion product, designed to match with other Minimal style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

DIMENSIONS

Height	140 mm
Width	596 mm
Depth	567 mm

FEATURES & BENEFITS

Complementary design

<>

Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

SPECIFICATIONS

Capacity	
Cappuccino cups	20
Espresso cups	42
Maximum allowable w	reight 25kg
Place settings	6
Usable depth	408mm
Usable height	98mm
Usable width	535mm

Cleaning

Easy clean smooth-glass base

Controls

Audio feedback	
Automatic pre-set	
Automatic timers	30', 45', 1h, 2h, 4h, 6l

Interior light LED Intuitive capacitive touch On/Off indicator Pre-set heating functions Push-to-open drawer Sabbath mode Standby mode Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage 10A Maximum power	Delayed start	•
On/Off indicator Pre-set heating functions Push-to-open drawer Sabbath mode Standby mode Functions Cups Dehydrate Number of functions Flates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage I oaar in indicator Power requirements Amperage Power requirements Amperage	Interior light	LED
Pre-set heating functions Push-to-open drawer Sabbath mode Standby mode Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage 10A	Intuitive capacitive touch	•
Push-to-open drawer Sabbath mode Standby mode Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage Amperage	On/Off indicator	•
Sabbath mode Standby mode Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage • Sabbath mode • Punctions • Amperage • Power requirements • • • • • • • • • • • • •	Pre-set heating functions	•
Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Standby mode Punctions 6 Plates Plates Performance Ferformance Fe	Push-to-open drawer	•
Functions Cups Dehydrate Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage 10A	Sabbath mode	•
Cups Dehydrate Number of functions Flates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range Power requirements Amperage Amperage	Standby mode	•
Dehydrate Number of functions 6 Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Functions	
Number of functions Plates Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Cups	•
Plates . Rapid proof . Slow cook . Warm . Performance Heated glass base and fan . Low temperature cooking . Temperature levels . Temperature range . Power requirements Amperage . 10A	Dehydrate	•
Rapid proof Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Number of functions	6
Slow cook Warm Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Plates	•
Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Rapid proof	•
Performance Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Slow cook	•
Heated glass base and fan Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Warm	•
Low temperature cooking Temperature levels Temperature range 35°C-85°C Power requirements Amperage 10A	Performance	
Temperature levels 6 Temperature range 35°C-85°C Power requirements Amperage 10A	Heated glass base and fan	•
Temperature range 35°C-85°C Power requirements Amperage 10A	Low temperature cooking	•
Power requirements Amperage 10A	Temperature levels	6
Amperage 10A	Temperature range	35°C-85°C
	Power requirements	
Maximum power 810W	Amperage	10A
	Maximum power	810W

1800mm

50/60Hz

3-prong grounding-type

Power cord length

Power outlet
Supply frequency

QUICK REFERENCE GUIDE > WB60SDEB2

Supply voltage	220-240V
Product dimensions	
Adjustable front door panel to	•
Depth	567 mm
Height	140 mm
Width	596 mm
Safety	
Automatic turn off after 12	•
Full extension telescopic	•
Warranty	
Parts and labour	2 years
SKU	82108

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1300 650 590 Wwww.fisherpaykel.com